



Optional 2-Unit (19 Inch) Rack Mount

The F50/50/9-4LCS Quad Fiber Passive TAP provides permanent access into a four multi-mode fiber links. This network TAP is ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network and non-powered, fiber TAPs will not affect network performance or integrity.

- Passive, non-powered design
- Four TAPs allow you to connect one tool per link; tools require a dual NIC card to receive both sides of the conversation
- Supports multiple topologies, including Gigabit Ethernet, ATM, OC3-OC48 and SONET
- View layer 1 and 2 errors not seen when performing network monitoring using SPAN ports
- Available with custom split ratios upon request
- Space saving design allows you to TAP up to eight links in 1U with two Quad Fiber Passive TAPs

TECHNICAL SPECIFICATIONS

TAP Connections

Four (4) OC3-OC48, 1000LX TAPs (LC)

Monitor Ports

Four (4) OC3-OC48, 1000LX (LC)

Split Ratio

50/50

Additional Split Ratios Available

Insertion Loss

4.0 dB Insertion Loss Max.

Physical Dimensions (HxWxD)

1.13 x 5.75 x 5.63 in (2.86 x 14.61 x 14.29 cm)

Weight

0.75 lbs (0.34 kgs)

Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)

Storage Temperature: -22° to 149°F (-30° to 65°C)

Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
F50/50/9-4LCS	Quad Fiber Passive TAP OC3-OC48, 1000LX (9 micron) 50/50 split ratio w/ LC Connectors
RMC-2	2 Tap 1U Rack Mount Chassis

ACCESS YOUR NETWORK™