



Eliminate clutter and organize your power connections with the Datacom Systems Multi-Unit Power Supply.

This easy to manage 1U power supply contains two (2) redundant hot-swappable power supplies and contains 12 lead power connections to provide dual redundant power for up to 12 Datacom Systems network taps or aggregators. Each power lead delivers up to 3 amps.

Includes cabling for 12 redundant device connections and DC power cords for devices located within 5U of the power supply.

- Powers up to 12 redundant power connections
- Easy to connect with included cabling set
- Universal power for global deployment
- Fits a standard 19" rack mount
- LEDs on hot-swappable power supplies confirm power status
- Compatible with Datacom Systems DC-powered units
- Fully RoHS compliant

TECHNICAL SPECIFICATIONS

Connectors	
24 - 5.0 VDC 3.0 A Receptacles	
Power Consumption Watts	
480.0	
BTU/h	
1636.8	
Electrical Specifications	
Output: 405-72.0VDC; 10.05-5.0A	
Certifications	
CE	
Physical Dimensions (HxWxD)	
1.75 x 19.00 x 13.00 in (4.45 x 48.26 x 33.02 cm)	
Weight	
10.0 lbs (4.54 kgs)	
Environment	
Operating Temperature: 32° to 104°F (0° to 40°C)	
Storage Temperature: -22° to 149°F (-30° to 65°C)	
Humidity: 5 to 90% non-condensing	
Warranty	
Two (2) Year Limited Warranty	
Order Information	
Product	Description
RPS-12-5-DC	Dual Redundant Rack Mountable DC Power Supply

ACCESS YOUR NETWORK™