



Optional 2-Unit (19 Inch) Rack

The SINGLEstream™ SS-1204BT-SFP Configurable Link Aggregation Tap enables any two connected monitoring devices to simultaneously monitor a full-duplex tapped 10/100/1000 link, using only one NIC per device.

Unlike traditional network taps, this in-line tap combines both sides of a full duplex data stream and hands the data off to up to two tools with single NICs, allowing monitoring systems with single channel NICs to view entire full-duplex transmissions.

An easy to use CLI provides access to dozens of features and settings, including port speed, port steering, and VLAN tag stripping.

- 24x7 access point for network monitoring and security tools
- Manage tap via networked management port or local serial port
- LINKprotect™ feature monitors network status and will allow the relay failover circuit to close if one or both sides of the network link go down, allowing your redundant network to re-route traffic automatically until the main network path is restored.
- “Any-to-Any” architecture on two (2) ports allows you to steer traffic as desired – configure one of your SFP ports to collect data from a SPAN port.
- Dual redundant, load balanced power supplies
- In-Line design eliminates contention for network access by freeing up SPAN/Mirror ports
- SFP connectors for the monitoring ports (“Any-to-Any” ports) are available in SX, LX, and RJ45, which will allow you to connect copper or fiber tools
- Standard split ratio 50/50 for fiber; others available upon request

TECHNICAL SPECIFICATIONS

Network Connection

One (1) RJ45 Tap

Monitor Ports

Two (2) SFP* Any-to-Any

Management Port (front)

RJ45 @ 100Mbps Full-Duplex

Serial Port (rear)

DB9F

Power Requirements

Two (2) External AC Adapters (Included)
 Input: 100-240VAC, 50-60 Hz, 0.4A-0.2A
 Output: 5VDC, 2.5A

Certifications

CE

Physical Dimensions (HxWxD)

1.10 x 8.00 x 7.00 in (2.79 x 20.32 x 17.78 cm)

Weight

1.6 lbs (0.7 kgs)

Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)
 Storage Temperature: -22° to 149°F (-30° to 65°C)
 Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
SS-1204SX-SFP	SINGLEstream™ Configurable Link Aggregation TAP (1- 10/100/1000 TAP, 2 - SFP Any-to-Any Ports)
RMC-2	2 TAP 1U Rack Mount Chassis
SFP's	SFP-LX, SFP-SX or SFP-RJ45 (Required Additional Purchase)

*SFP = Small Form Pluggable

ACCESS YOUR NETWORK™

9 Adler Drive ■ East Syracuse, NY 13057 ■ T: (315) 463-9541 ■ F: (315) 463-9557 ■ DatacomSystems.com