



Optional 2-Unit (19 Inch) Rack

The SINGLEstream™ SS-2206SX-SFP Configurable Dual Link Aggregation Tap enables up to two (2) connected monitoring devices to simultaneously monitor two (2) full-duplex tapped SX links, using only one NIC per device.

Unlike traditional network taps, this in-line tap combines both sides of a full duplex data stream and hands the data off to up to two tools with single NICs, allowing monitoring systems with single channel NICs to view entire full-duplex transmissions.

An easy to use CLI provides access to dozens of features and settings, including port speed, port steering, and VLAN tag stripping.

- 24x7 access point for network monitoring and security tools
- Manage tap via networked management port or local serial port
- “Any-to-Any” architecture on two (2) ports allows you to steer traffic as desired – configure any of your SFP ports to collect data from a SPAN port
- Dual redundant, load balanced power supplies
- In-Line design eliminates contention for network access by freeing up SPAN/Mirror ports
- SFP connectors for the monitoring ports (“Any-to-Any” ports) are available in SX, LX, and RJ45, which will allow you to connect copper or fiber tools
- Standard split ratio 50/50 for fiber; others available upon request

## TECHNICAL SPECIFICATIONS

### Network Connections

Two (2) Dual LC Taps

### Monitor Connections

Two (2) SFP\* Any-to-Any Ports

### Management Port (front)

RJ45 @ 100Mbps Full-Duplex

### Serial Port (rear)

DB9F

### Power Requirements

Two (2) External AC Adapters (Included)  
 Input: 100-240VAC, 50-60 Hz, 0.4A-0.2A  
 Output: 5VDC, 2.5A

### Certifications

CE

### Physical Dimensions (HxWxD)

1.10 x 8.00 x 7.00 in (2.79 x 20.32 x 17.78 cm)

### Weight

1.6 lbs (0.7 kgs)

### Environmental

Operating Temperature: 32° to 104°F ( 0° to 40°C)  
 Storage Temperature: -22° to 149°F (-30° to 65°C)  
 Humidity: 5 to 90% non-condensing

### Warranty

Two (2) Year Limited Warranty

### Order Information

Product	Description
SS-2206SX-SFP	SINGLEstream™ Configurable Dual Link Aggregation TAP (2- SX Taps, 2 - SFP Any-to-Any Ports)
RMC-2	2 TAP 1U Rack Mount Chassis
SFP's	SFP-LX, SFP-SX or SFP-RJ45 (Required Additional Purchase)

\*SFP = Small Form Pluggable

## ACCESS YOUR NETWORK™

9 Adler Drive ■ East Syracuse, NY 13057 ■ T: (315) 463-9541 ■ F: (315) 463-9557 ■ DatacomSystems.com