



Configurable (XFP) “Any-to-Any” Ports



Dual Redundant Hot Swappable Power Supplies Serial Ports Management Port Upgradable Management Card

AGGREGATION

The VERSAstream™ 1204-10Gb can combine data from multiple 10 Gigabit Ethernet network segments into one or more streams of data. Connected devices, such as intrusion detection systems, protocol analyzers, or network probes can receive the aggregated data with just one network interface card (NIC) per device.

REGENERATION

With four (4) configurable ports the VS-1204-10Gb can be configured to have multiple monitoring ports to allow connected devices to receive multiple copies of the same data stream. Allowing multiple monitoring and analysis devices to collect data from the same network segments at the same time eliminates contention for SPAN ports.

PORT STEERING

The Any-to-Any port architecture of the VS-1204-10Gb allows you to send traffic to any port from any other port. This provides maximum flexibility and eliminates the need for network personnel to manage or change complex configurations of SPAN ports or move tools around their network.

- 24X7 access point for network monitoring and security tools
- Any-to-Any architecture can send traffic to any port from any other port, eliminating the need for network managers to manage or change complex configurations of SPAN ports or move tools around their network.
- “Many-to-Any” architecture combines traffic from multiple ports, providing visibility into multiple network connections
- “One-to-Many” architecture allows the end user to send multiple copies of data from the input port to multiple monitoring devices
- Hot swappable dual redundant load balanced power supplies
- Hot swappable management card compatible with filtering upgrade

TECHNICAL SPECIFICATIONS

Configurable Any-to-Any Ports

Four (4) XFP

Management Port (front)

RJ45 @ 100Mbps Full-Duplex

Serial Ports (rear)

DB9F and DB9M

Power Requirements

Input: 100-240VAC, 50-60Hz, 0.4-0.2A

Certifications

CE

Physical Dimensions (HxWxD)

1.75 x 19.00 x 21.00 in (4.45 x 48.26 x 53.35 cm)

Weight

13.5 lbs (6.12 kgs)

Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)
Storage Temperature: -22° to 149°F (-30° to 65°C)
Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
VS-1204-10G	VERSAstream™ 10 Gigabit Data Access Switch (4 - XFP Any-to-Any Ports)
XFPs	XFP-SR or XFP-LR (Required Additional Purchase)