



Optional 2-Unit (19 Inch) Rack Mount

AGGREGATION

The VERSAstream™ 1208BT Data Access Switch can combine data from multiple Ethernet network segments into one stream of data. A single device, such as an intrusion detection system, protocol analyzer, or network probe can receive the aggregated data with just one network interface card (NIC).

REGENERATION

With six (8) 10/100/1000 ports, the VS-1208BT can be configured to have multiple monitoring ports to allow connected devices to receive multiple copies of the same data stream. Allowing multiple monitoring and analysis devices to collect data from the same network segments at the same time, eliminates contention for SPAN ports.

PORT STEERING

The Any-to Any port architecture of the VS-1208BT allows you to send traffic to any port from any other port. This provides maximum flexibility and eliminates the need for network personnel to manage or change complex configurations of SPAN ports or move tools around their network.

- 24X7 access point for network monitoring and security tools
- Any-to-Any architecture can send traffic to any port from any other port, eliminating the need for network managers to manage or change complex configurations of SPAN ports or move tools around their network.
- “Many-to-Any” architecture combines traffic from multiple ports, providing visibility into multiple network connections
- “One-to-Many” architecture allows the end user to send multiple copies of data from the input port to multiple monitoring devices
- Dual redundant load balanced power supplies

TECHNICAL SPECIFICATIONS

Any-to-Any Ports

Eight (8) 10/100/1000 (RJ45)

Management Port (front)

RJ45 @ 100Mbps Full-Duplex

Serial Port (rear)

DB9F

Power Requirements

Two (2) External AC Adapters (Included)
 Input: 100-240VAC, 50-60Hz, 0.6-0.3A
 Output: 5VDC, 2A

Certifications

CE

Physical Dimensions (HxWxD)

1.10 x 8.00 x 7.00 in (2.79 x 20.32 x 17.78 cm)

Weight

1.6 lbs (0.7 kgs)

Environment

Operating Temperature: 0° to 40°C (32° to 104°F)
 Storage Temperature: -30° to 65°C (-22° to 149°F)
 Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
VS-1208BT	VERSAstream™ 10/100/1000 8-Port Data Access Switch (8 - 10/100/1000 Any-to-Any Ports)
RMC-2	2 TAP 1U Rack Mount Chassis

ACCESS YOUR NETWORK™